



## 400 KW / 500 KVA POWERED by



MODEL		TP-P400-T3-60	
<p>Triton Power is a world leader in the design, manufacture of stationary, mobile and rental generator sets and Power Modules from 10 to 2000 kW. Through our commitment to quality we manufacture with only the highest quality components from companies like Cummins, John Deere, Perkins, Marathon, and Deep Sea. All of this plus our worldwide warranty, customer service professionals, is why Triton is the</p> <p><b>THE POWER OF QUALITY</b></p>			
<p>Available Voltage 3 Phase 120/208, 110/220, 120/240, 277/480 Power Factor 0.8</p>	Standby	kVA	500
		kW	400
	Prime	kVA	450
		kW	360

**Standby** : Continuous running at variable load for duration of an emergency. No overload is permitted on these ratings. In accordance with ISO 3046 .

**Prime** : Continuous running at variable load for unlimited periods with 10% overload available for 1 hour in any 12 hour period. In accordance with ISO 8528, ISO 3046.

- High quality, reliable and complete power unit
- Compact design
- Easy start and maintenance
- Every generator set is subject to a comprehensive test program which includes full load testing and checking and providing of all control and safety shut down functions testing
- Full engineered with a wide range of options and accessories:
  - Sound Attenuated Enclosure
  - Trailer with fuel tank
  - UL Listed Fuel Tank
  - Permanent Magnet Generator
  - Electronic Governor



Manufacturer reserves the right to make changes in model, technical specifications, color, equipment and accessories without prior notice.  
All photos are representative and may not reflect exact model



ENGINE INFORMATION		
<b>ENGINE MAKE</b>		<b>PERKINS</b>
<b>Model</b>		<b>2206D-E13TAG3</b>
<b>Engine Speed</b>	<b>RPM</b>	<b>1800</b>
<b>Tier Rating</b>		<b>Tier 3</b>
<b>Engine Power Output at rated rpm</b>	<b>kWm</b>	<b>462</b>
	<b>HP</b>	<b>620</b>
<b>Cooling</b>		<b>Radiator Cooled</b>
<b>Aspiration</b>		<b>Turbocharged &amp; Air-to-air charge cooled</b>
<b>Total Displacement</b>	<b>Liter</b>	<b>12.5</b>
<b>No. of Cylinders and Build</b>		<b>6-inline</b>
<b>Bore and Stroke</b>	<b>mm x mm</b>	<b>130 x 157</b>
<b>Compression Ratio</b>		<b>16.3:1</b>
<b>Governor</b>		<b>Electronic</b>
<b>Fuel Consumption (L/hr)</b>	<b>Full Load</b>	<b>94</b>
	<b>75% Load</b>	<b>73</b>
	<b>50% Load</b>	<b>52</b>
<b>Fuel Tank Capacity (Non-UL)</b>	<b>Liter</b>	<b>900 Open / 800 SAE</b>
<b>Oil Capacity</b>	<b>Liter</b>	<b>40</b>
<b>Coolant Capacity</b>	<b>Liter</b>	<b>51.4</b>
<b>Radiator Cooling Air</b>	<b>m<sup>3</sup>/min</b>	<b>788</b>

<p><u>Economic Power</u></p> <ul style="list-style-type: none"> <li>Mechanically operated unit fuel injectors with electronic control, combined with carefully matched turbo-charging, provide excellent fuel economy and low emissions.</li> </ul> <p><u>Reliable Power</u></p> <ul style="list-style-type: none"> <li>Developed and tested using the latest engineering techniques and finite element analysis for high reliability, low oil usage and low wear rates.</li> <li>High compression ratios ensure clean rapid starting in all conditions.</li> </ul>	<p><u>Compact, Clean and Efficient Power</u></p> <ul style="list-style-type: none"> <li>Exceptional power to weight ratio and compact size give optimum power density for ease of installation and more cost effective transportation.</li> <li>Designed to provide excellent service access for ease of maintenance.</li> </ul> <p><u>Product Support</u></p> <ul style="list-style-type: none"> <li>Total worldwide service is provided through a network of 4,000 distributors and dealers.</li> <li>TIPSS - The Integrated Parts and Support System enables customers to specify and order parts electronically as well as service engines with on-line guides and service tools.</li> </ul>
---	--



## CONTROLLER INFORMATION DEEP SEA MODEL 7420

The DSE7420 is an Auto Mains (Utility) Failure Control Module suitable for a wide variety of single, diesel or gas, gen-set applications. A sophisticated module monitoring an extensive number of engine parameters, the DSE74xx will annunciate warnings, shutdown and engine status information on the back-lit LCD screen, illuminated LED, remote PC, audible alarm and via SMS text alerts. The module includes RS232, RS485 & Ethernet ports as well as dedicated terminals for system expansion.

### MAIN FEATURES:



- |   |   |
|---|---|
| <ul style="list-style-type: none"> <li>• Configurable inputs (11)</li> <li>• Configurable outputs (8)</li> <li>• Voltage measurement</li> <li>• Mains (utility) failure detection</li> <li>• Dedicated load test button</li> <li>• kW overload alarms</li> <li>• Comprehensive electrical protection</li> <li>• RS232, RS485 &amp; Ethernet remote communications</li> <li>• Modbus RTU/TCP</li> <li>• PLC functionality</li> <li>• Multi event exercise timer</li> <li>• Back-lit LCD 4-line text display</li> <li>• Multiple display languages</li> <li>• Automatic start/Manual start</li> <li>• Audible alarm</li> <li>• Fixed and flexible LED indicators</li> <li>• Event log (250)</li> <li>• Engine protection</li> <li>• Fault condition notification to a designated PC</li> <li>• Font panel mounting</li> <li>• Protected front panel programming</li> <li>• Configurable alarms and timers</li> <li>• Configurable start and stop timers</li> <li>• Five key menu navigation</li> <li>• Front panel editing with PIN protection</li> <li>• 3 configurable maintenance alarms</li> <li>• CAN and Magnetic Pick-up/Alt. sensing</li> </ul> | <ul style="list-style-type: none"> <li>• Fuel usage monitor and low fuel alarms</li> <li>• Charge alternator failure alarm</li> <li>• Manual speed control (on compatible CAN engines)</li> <li>• Manual fuel pump control</li> <li>• “Protections disabled” feature</li> <li>• Reverse power protection</li> <li>• Power monitoring (kW h, kV Ar, kV A h, kV Ar h)</li> <li>• Load switching (load shedding and dummy load outputs)</li> <li>• Automatic load transfer</li> <li>• Unbalanced load protection</li> <li>• Independent Earth Fault trip</li> <li>• Fully configurable via DSE Configuration Suite PC software</li> <li>• Configurable display languages</li> <li>• Remote SCADA monitoring via DSE Configuration Suite PC software</li> <li>• Advanced SMS messaging (additional external modem required)</li> <li>• Start &amp; stop capability via SMS messaging</li> <li>• Additional display screens to help with modem diagnostics</li> <li>• DSENet® expansion compatible</li> <li>• Integral PLC editor</li> </ul> |
|---|---|

### BENEFITS

- |   |   |
|---|---|
| <ul style="list-style-type: none"> <li>• RS232, RS485 &amp; Ethernet can be used at the same time</li> <li>• DSENet® connection for system expansion</li> <li>• PLC functionality</li> <li>• Five step dummy load support</li> <li>• Five step load shedding support</li> </ul> | <ul style="list-style-type: none"> <li>• Worldwide language support</li> <li>• Direct USB connection to PC</li> <li>• Ethernet monitoring</li> <li>• USB host</li> <li>• Data logging &amp; trending</li> </ul> |
|---|---|

### OPERATION

The module is operated using the front STOP/RESET, MANUAL, AUTO, TEST and START pushbuttons. An additional pushbutton next to the LCD display is used to scroll through the modules metering displays.



## ALTERNATOR INFORMATION

Manufacturer	Stamford Newage - HCI444F
Design	Brushless single bearing, revolving field
Stator	2/3 pitch
Rotor	Single bearing, flexible disc
Insulation System	Class H
Standard Temperature Rise	125 -163°C Continuous
Exciter Type	Self Excited
Phase Rotation	A (U), B (V), C (W)
Alternator Cooling	Direct drive centrifugal blower fan
AC Waveform Total Harmonic Distortion	No load < 1.5%. Non distorting balanced linear load < 5%
Telephone Influence Factor (TIF)	<50 per NEMA MG1-22.43
Telephone Harmonic Factor (THF)	<2%

## STANDARD ITEMS

- Mainline Circuit Breaker
- Generator Set mounted on Heavy Duty Steel Base Frame
- Anti-Vibration Pads between Engine/Alternator and Frame
- 8 to 10 Hour Base Fuel Tank (up to 600 kW)
- Forklift Pockets within Base Frame (up to 400 kW)
- Battery Charging Alternator


## OPTIONAL ITEMS

ENGINE OPTIONS	<ul style="list-style-type: none"> <li>• Engine Block Heater</li> <li>• Racor Fuel Water Separator</li> <li>• Oil Heater</li> </ul>
ALTERNATOR OPTIONS	<ul style="list-style-type: none"> <li>• Permanent Magnet Generator</li> <li>• Anti-Condensation Heater</li> <li>• Oversized Alternator (Motor Starting)</li> </ul>
OTHER OPTIONS	<ul style="list-style-type: none"> <li>• Sound Attenuated Enclosure with Critical Silencer (70 db at 7 meters)</li> <li>• Trailer (with or without fuel tank)</li> <li>• UL-142 Base Mounted Fuel Tank</li> <li>• Residential or Critical Grade Silencer</li> </ul>


Manufacturer reserves the right to make changes in model, technical specifications, color, equipment and accessories without prior notice.  
 All photos are representative and may not reflect exact model



# WEIGHT AND DIMENSIONS



SKID MOUNTED GENERATOR		
DIMENSIONS (LxWxH)	mm	3420 x 1210 x 2150
DRY WEIGHT	kg	3080



SOUND ATTENUATED GENERATOR		
DIMENSIONS (LxWxH)	mm	4242 x 1463 x 2512
DRY WEIGHT	kg	4471

**FEATURES AND BENEFITS OF ENCLOSURE:**

- |  |   |
|--|---|
| <ul style="list-style-type: none"> <li>• All enclosure parts are modular</li> <li>• No welding to reduce corrosion</li> <li>• Doors on both sides for easy maintenance</li> <li>• All metal parts are powder coated</li> </ul> | <ul style="list-style-type: none"> <li>• Critical Exhaust Silencer Included</li> <li>• Thermally insulated exhaust system</li> <li>• Emergency stop located on exterior</li> <li>• Easy Lifting and Moving</li> </ul> |
|--|---|



**TRITON POWER CORP**  
 8511 NW 61 STREET MIAMI, FL USA  
 305-592-6300 Fax: 305-592-5900 email: [info@tritonpower.com](mailto:info@tritonpower.com)  
[www.gopower.com](http://www.gopower.com)

Triton Power is a subsidiary of Americas Generators, Inc.

Manufacturer reserves the right to make changes in model, technical specifications, color, equipment and accessories without prior notice.  
 All photos are representative and may not reflect exact model